

SLB38-12 [12V-38Ah]

SLB 12-38 Battery

Specification


Cells Per Unit	6
Voltage Per Unit	12
Capacity	38Ah@10hr-rate to 1.80V per cell @25°C ^o
Weight	Approx. 12.4 Kg(Tolerance)±3%
Max. Discharge Current	380A (5 sec)
Internal Resistance	Approx. 8 mΩ
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ± 5°C
Float charging Voltage	13.6 to 13.8 VDC/unit Average at 25°C
Recommended Maximum Charging Current	12 A
Equalization and Cycle Service	14.6 to 14.8 VDC/unit Average at 25°C
Self Discharge	Valve Regulated Lead Acid (VRLA) batteries can be stored for more than 6 months at 25°C. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminal	Terminal F4/F11
Container Material	A.B.S. UL94-HB, UL94-VO Optional.



SLB38-12 (12V-38Ah) is a general purpose battery with 10 years design life in float service or more than 260 cycles at 100% discharge in cycle service. It meets with IEC, JIS and BS standards.

With up-dated AGM valve regulated technology and high purity raw materials, the battery maintains high consistency for better performance and reliable standby service life. It is suitable for UPS/EPS, medical equipment, emergency light and security system applications.

Dimensions 198mm(L) x 166mm(W) x 171mm(H)



Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75V	1.70V	1.60V
Discharge Current (A)	(A) ≤0.2C	0.2C < (A) < 1.0C	(A) ≥1.0C

Charge the batteries at least once every six months, if they are stored at 25°C.

Charging Method:

Constant Voltage	-0.2Cx2h+14.4-14.7Vx24h, Max. Current 0.3C
Constant Current	-0.2Cx2h+0.1Cx12h
Fast	-0.2Cx2h+0.3Cx4h

Bolt	M5	M6	M8
Terminal	F3 F4 F13 F18 T25 T26	F8 F11 F12-1 F15	F5 F9 F10 F12 F14 F16
Torque	6~7N·m	8~10N·m	10~12N·m

Maintenance & Cautions

Float Service:

- * Every month, recommend inspection every battery voltage.
- * Every three months, recommend equalization charge for one time.

Equalization charge method:

- Discharge: 100% rate capacity discharge.
- Charge: Max. current 0.3CA, constant voltage 14.4-14.7V charge 24h.
- * Effect of temperature on float charge voltage: -3mV/°C/Cell.
- * Length of service life will be directly affected by the number of discharge cycles, depth of discharge, ambient temperature and charging voltage.



G4M20206-0910E-16



MI28539




SLB38-12 (12V-38Ah)


SLB 12-38 Battery




Effect of temperature on long term float life




Storage characteristic



Charge characteristic Curve for standby use



Discharge characteristic Curve



Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V&12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V&12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

Constant Current Discharge Characteristics: A (25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	133.1	98.99	74.62	39.38	24.97	15.41	10.48	8.447	7.012	4.618	4.162	2.204
10.0V	129.2	94.19	73.09	38.88	24.64	15.10	10.28	8.327	6.949	4.600	4.122	2.162
10.2V	125.4	90.87	71.94	38.29	24.40	14.94	10.19	8.244	6.904	4.559	4.081	2.121
10.5V	112.6	83.85	68.49	37.23	24.10	14.75	10.10	8.122	6.846	4.518	4.040	2.080
10.8V	101.6	76.46	63.14	36.00	23.77	14.63	9.982	7.844	6.812	4.500	4.003	2.059
11.1V	86.77	68.33	56.63	34.63	23.20	14.04	9.786	7.731	6.763	4.464	3.957	1.976

Constant Power Discharge Characteristics: W (25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	1404	1054	813.4	450.8	289.3	180.6	123.3	101.1	84.00	55.31	49.91	26.54
10.0V	1376	1022	800.4	446.2	286.7	178.4	121.5	99.7	83.25	55.09	49.52	26.08
10.2V	1360	995.0	791.4	442.3	285.0	177.2	121.0	98.7	82.74	54.68	49.08	25.60
10.5V	1238	926.5	754.8	433.3	283.2	174.9	120.0	97.4	82.08	54.21	48.60	25.12
10.8V	1128	854.1	697.7	423.0	279.5	173.6	118.6	94.1	81.70	53.98	48.12	24.87
11.1V	990.7	772.2	628.0	411.1	275.3	167.1	116.6	92.78	81.41	53.60	47.59	23.98

All mentioned values are average values

(Tolerance ±2%).